ENBECK

ALUMINUM PRODUCTS

SPECIFICATIONS



Aluminum Utility Trailers

	5x8 SA	5x10 SA	6x10 SA	6x12 SA	6x12 TA	6x14 SA
Overall Length	13'	15'	15'	17'	17'	19'
Overall Width	81"	81"	94"	94"	94"	94"
Overall Height	37.5"	37.5"	37.5"	37.5"	37.5"	37.5"
Inside Length	97"	121"	121"	145"	145"	169"
Inside Width	60"	60"	72"	72"	72"	72"
Inside Height	20.5"	20.5"	20.5"	20.5"	20.5"	20.5"
Platform Height	17"	17"	17"	17"	17"	17"
Axle	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension	Spring	Spring	Spring	Spring	Spring	Spring
Brakes	No	No	No	No	Yes	No
Frame	2"x3"	2"x3"	2"x3"	2"x3"	2"x4"	2"x3"
Tire Size	15"	15"	15"	15"	15"	15"
Hitch Ball Size	2"	2"	2"	2"	2 5/16"	2"
Est. Curb Weight kg/lbs	286/630	310/689	330/727	390/860	425/936	454/1000
Est Hitch Weight lbs	50	60	60	65	75	75
GVWR	3500	3500	3500	3500	7000	3500
Payload Capacity	2870	2811	2773	2640	6064	2500
Tie Downs	6	8	8	8	8	8

	7x12 SA	7x12 TA	7x14 SA	7x14 TA	7x16 TA	7x18 TA	7x20 TA
Overall Length	17'	17'	19'	19'	20.7'	22.5'	24.5'
Overall Width	102"	102"	102"	102"	102"	102"	102"
Overall Height	37.5"	37.5"	37.5"	37.5"	37.5"	37.5"	37.5"
Inside Length	145"	145"	169"	169"	193"	216"	240"
Inside Width	80"	80"	80"	60"	80"	80"	80"
Inside Height	20.5"	20.5"	20.5"	20.5"	20.5"	20.5"	20.5"
Platform Height	17"	17"	17"	17"	17"	17"	17"
Axle	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Brakes	No	Yes	No	Yes	Yes	Yes	Yes
Frame	2"x3"	2"x4"	2"x4"	2"x4"	2"x4"	2"x4"	2"x4"
Tire Size	15"	15"	15"	15"	15"	15"	15"
Hitch Ball Size	2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 516"
Est. Curb Weight kg/lbs	475/1047	475/1047	500/1102	550/1212	600/1322	675/1488	750/1653
Est Hitch Weight lbs	70	70	75	60	65	75	75
GVWR	3500	3500	3500	7000	7000	7000	7000
Payload Capacity	2453	2453	2398	5788	5678	5512	5347
Tie Downs	8	8	8	8	10	10	10

Side Load Models

	7x14 SASL	7x14 TASL	7x16 TASL	7x18 TASL
Overall Length	19'	19'	20.7'	22.5'
Overall Width	102"	102"	102"	102"
Overall Height	37.5"	37.5"	37.5"	37.5"
Inside Length	169"	169"	193"	216"
Inside Width	80"	80"	80"	80"
Inside Height	20.5"	20.5"	20.5"	20.5"
Platform Height	17"	17"	17"	17"
Axle	4" Drop	4" Drop	4" Drop	4" Drop
Suspension	Spring	Spring	Spring	Spring
Brakes	No	Yes	Yes	Yes
Frame	2"x4"	2"x4"	2"x4"	2"x4"
Tire Size	15"	15"	15"	15"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Est. Curb Weight kg/lbs	500/1102	550/1212	600/1322	675/1488
Est Hitch Weight lbs	85	90	95	95
GVWR	3500	7000	7000	7000
Payload Capacity	2398	5788	5678	5512
Tie Downs	8	8	10	10

STANDARD FEATURES:

*** all measurements are approximate****

- Square Tube Top Rail
- Mesh Ramp Gate
- 3500lb 4" Drop Spring Leaf Axles
- EZ Lube Hubs
- LED Lights
- Fully Sealed Wiring Harness
- Electric Brakes (On Tandem Axle Trailers)
- 15" Radial Tires
- Hardwood Decking
- Welded Tie Downs
- A-Frame Tongue w/ Double Frame support to Axle
- 16" on Centre Crossmembers
- Fully Welded Interior Box
- Aluminium Rims

ADDITIONAL OPTIONS:

- Aluminum Tool Box
- Aluminum Spare Tire
- Galvanized Spare Tire
- Wheel Jack